



Screwless Connectors
Luminaire Connectors

LK 980-01/ 2 printed "N L"

terminal block, 2 pole, insulating material: PA 6.6, fixing: screw,
printing: N L, voltage rating: 450 V, current rating: 24 A, cross-section
rating: 2.5 mm²



Order Info

reference number (ref. no.)	041012
Applications	Lighting, Electrical Appliances
PU	600
EAN	4028012102570

Type

type	terminal block
number of poles	2 pole
clamping units per pole	2
colour	white
cross-section rating	2.5 mm ²
printing	N L

Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA 6.6
contact material	Spring Steel, Copper
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
stripping length	8.0-9.0 mm
internal core cross-section max.	1.5 / 2.5 mm ²
external core cross-section min.	0.5 mm ²
external core cross-section max.	2.5 mm ²
fixing	screw
internal core cross-section min.	0.5 mm ²
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Stranded External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes

Approbation EN60998	LK980-01_EN60998_20070627_20101213_VDE_ENEC_40021343_v
Approbation UL	LK980_20010625_20110411_UL_E63492_1-18_Description_web.pdf

Accessories

WKZ 980-01	999041
ZEL 110	196420
ZEL 900	196423