



Product: <u>8669</u> ☑

Shielding & Bonding, TC Braid #8.9AWG

😭 Request Sample

Product Description

Shielding & Bonding, TC Braid 8.9AWG (336x34)

Technical Specifications

Physical Characteristics (Overall)

Conductor AWG Stranding Material					
8.9336x34TC - Tinned Copper					
Conductor Count:	1				
Insulation					
Material No Insulation					
Construction and Dimensions					
Braided Tubular I.D.1:	0.5 in				
Circular Mil Area (CMA)1:	13300				
Electrical Characteristics					
Conductor DCR					
0.78 Ohm/1000ft Current Max. Recommended Current [A] 62.0 A Mechanical Characteristics					
Bulk Cable Weight:	45.6 lbs/1000ft				
Standards					
UL AWM Style:	N/A				
Military Specification:	N/A				
Applicable Environmental and	Other Programs				
EU Directive 2000/53/EC (ELV):	Yes				
EU Directive 2003/96/EC (BFR):	Yes				
EU Directive 2011/65/EU (ROHS II):	Yes				
EU Directive 2012/19/EU (WEEE):	Yes				
EU Directive 2015/863/EU:	Yes				
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)				
EU CE Mark:	Yes				

EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL voltage rating:	N/A
Plenum/Non-Plenum	

Plenum (Y/N): No

Part Number

Variants				
Item #	Color	Putup Type	Length	UPC
8669 00050	None	Reel	50 ft	612825213987
8669 000250	None	Reel	250 ft	612825213970
Footnote:			C	C - CRATE REEL
Footnote:	Footnote:			- MAY CONTAI

Product Notes

Notes:	AWG size is approximated.		
History			
Update and Revision:	Revision Number: 0.265 Revision Date: 04-28-2020		

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulatory based on their individual usage of the product.