

15505.2

PSC 1/24V DC-24V/2A/DC

PSC 1/24V DC-24V/2A/DC



Plug-in miniature solid-state relay, power solid-state relay, 1 NO contact, Input: 24 VDC, Output: 24 VDC/2 A

Business data

Product description	Solid-state module
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	3.6
Weight per piece (including packaging)	4.97
Unit of weight	G
Customs number	85364900
Country of origin	EEC

15505.2

PSC 1/24V DC-24V/2A/DC

PSC 1/24V DC-24V/2A/DC

Technical Data

Dimensions

Length	28 mm
Width	5 mm
Height	15 mm

Input data

Input voltage	24 VDC
Drop-out voltage	10 VDC
Control current	7,2 mA
Number of channels	1
Operating range	16-30 VDC
Power consumption	0,17 W

Output data

Output voltage range	1,5-24 VDC V
Voltage drop at 20 °C and rated current, max.	0,12 V
Switching current, min.	0,001 A
Continuous current max. / Inrush current max.	2 / 40 A
Residual current at 55 °C, max.	0,001 mA

Materials

Working temperature, min.	-20 °C
Working temperature, max.	55 °C

Further technical data

Response/release time	0,1 / 0,6 ms
Remarks	1 NO contact
Test voltage	2.5 kV

15505.2

PSC 1/24V DC-24V/2A/DC

PSC 1/24V DC-24V/2A/DC

Media

