

3089.0

H 16,0/25,5 KS BU

H 16,0/25,5 KS BU



Wire-end ferrules, Max. wire cross-section: 16 mm², Length: 25.5 mm, Length of copper pipe: 12 mm, Colour: Blue

Business data

| | |
|--------------------------------------------|----------|
| Product description | Ferrules |
| Packaging unit | 100 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 0.96 |
| Weight per piece (including packaging) | 1 |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | DE |

3089.0

H 16,0/25,5 KS BU

H 16,0/25,5 KS BU

Technical Data

Dimensions

| | |
|----------------------------------|---------|
| Length | 25.5 mm |
| Length of copper pipe | 12 mm |
| Diameter of copper pipe | 6 mm |
| Diameter plastic collar | 11.9 mm |
| Wall thickness of copper pipe | 0.2 mm |
| Wall thickness of plastic collar | 0.3 mm |

Connection data

| | |
|------------------------------|--------------------|
| Wire cross-section, max. | 16 mm ² |
| Wire cross-section AWG, max. | 6 |
| Stripping length | 12 mm |

Materials

| | |
|---------------------------|--------------------------------|
| Copper pipe | Copper alloy |
| Surface | Galvanically tin-plated, shiny |
| Plastic collar | Polypropylene homopolymer |
| Working temperature, min. | -5 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

3089.0

H 16,0/25,5 KS BU

H 16,0/25,5 KS BU

Approvals

Standards and regulations

DIN 46228-4:1990

✓