

## Specification Sheet

Part Number: 151-01317



Push Pin, Mounting Hole Dia. 6.5mm, PA66HIRHSUV, Black, 5000/carton

**Article Number** 151-01317

**Type** FT6.5 Plug

**Color** Black (BK)

**Features & Benefits**

- Low insertion force enables fast, tool-less mounting.
- High extraction resistance means clamp and mount stay put.
- Top disc covers mounting hole and minimizes ingress of dust, dirt and water.

**Quantity Per** carton

**Product Description**

The Push Pin is a convenient fir tree fastener used to secure the Ratchet P-Clamp with metal base plate to a surface with a 6.5 mm hole.

<b>Short Description</b>	Push Pin, Mounting Hole Dia. 6.5mm, PA66HIRHSUV, Black, 5000/carton
<b>Global Part Name</b>	FT6.5 Plug-PA66HIRHSUV-BK
<b>Minimum Tensile Strength (Imperial)</b>	25
<b>Minimum Tensile Strength (Metric)</b>	110
<b>Length L (Imperial)</b>	0.76
<b>Length L (Metric)</b>	18.60
<b>Width W (Imperial)</b>	0.62
<b>Width W (Metric)</b>	15.7
<b>Height H (Imperial)</b>	0.48
<b>Height H (Metric)</b>	12.5
<b>Panel Thickness Min(Imperial)</b>	0.02
<b>Panel Thickness Max(Imperial)</b>	0.24
<b>Panel Thickness Min (Metric)</b>	0.60
<b>Panel Thickness Max (Metric)</b>	6.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 - 0.27

**Mounting Hole Diameter D (Metric)** 6.1 - 6.9 mm

**Mounting Hole Diameter D Min (Imperial)** 0.24

**Mounting Hole Diameter D Max (Imperial)** 0.27

**Mounting Hole Diameter D Max (Metric)** 6.9

**Disc Diameter(Metric)** 18.6

**Disc Diameter (Imperial)** 0.73

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Flammability** UL 94 HB

**Operating Temperature (Metric)** -40°F to +221°F (-40°C to +105°C)

**Package Quantity(Imperial)** 5000

**Package Quantity (Metric)** 5000

**Customs Number** 3926909988

**Content Unit(BMEcat)** pcs.

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)