

## Specification Sheet

Part Number: TSRP2I-6A



One Piece Power Rated Raceway, 1-1/4", 6.0 ft Long, PVC, Ivory, 120ft/Carton

**Article Number** 250-62601

**Type** TSRP2-6A

**Color** Ivory (IV)

### Features & Benefits

- Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick re-entry as well as providing a secure installation of power cables.
- U.L. Listed for power up to 600 Volts, meeting UL5A and CSA 22.2 Number 62-93 Standards.
- Manufactured from UL 94V-0 rated PVC material.
- Fittings incorporate a minimum 1" bend radius per TIA/EIA 568-B and 569-A standards.
- Large base for greater adhesive surface.
- Rubber-based foam tape adhesive with high ultimate bond strength, which conforms to any surface.
- Flexible hinge allows the raceway to endure numerous openings without creating discoloration or stress cracking.
- Junction boxes can be used for electrical or data outlets.
- Designed to complement HellermannTyton's industry standard TSR low voltage raceway system.

|                            |  |
|----------------------------|--|
| <b>Quantity Per</b>        | carton   |
| <b>Product Description</b> | HellermannTyton's TSRP power surface raceway is a one piece, non-metallic, adhesive backed latching raceway designed to aesthetically organize and route either power or communications cables. Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick reentry as well as providing a secure installation of power cables. |
| <b>Short Description</b>   | One Piece Power Rated Raceway, 1-1/4", 6.0 ft Long, PVC, Ivory, 120ft/Carton   |
| <b>Global Part Name</b>    | TSRP2-6A-PVC-BGE   |
| <b>Length L (Imperial)</b> | 6.0  |
| <b>Length L (Metric)</b>   | 1.83   |
| <b>Width W (Imperial)</b>  | 1.25   |
| <b>Width W (Metric)</b>    | 31.75  |
| <b>Height H (Imperial)</b> | .75  |
| <b>Height H (Metric)</b>   | 19.05  |
| <b>Material</b>            | Polyvinylchloride (PVC)  |
| <b>Material Shortcut</b>   | PVC  |

|                                       |                |
|---------------------------------------|----------------|
| <b>Flammability</b>                   | UL 94 V0       |
| <b>Halogen free</b>                   | No             |
| <b>Operating Temperature (Metric)</b> | +122°F (+50°C) |
| <b>Reach Complaint(Article 33)</b>    | No             |
| <b>ROHS Complaint</b>                 | Yes            |
| <b>UL Listed (US and Canada)</b>      | Yes            |
| <b>UL Listed (US</b>                  | Yes            |
| <b>Package Quantity(Imperial)</b>     | 120            |
| <b>Package Quantity (Metric)</b>      | 36.58          |
| <b>Customs Number</b>                 | 3925900000     |