

REPLACES	1XE311	
	M	RELEASE NO. PR-20431
DRAWING NUMBER	3	
	ISSUE	CHECK
REVISIONS	ADD NOTE 5	
	NWJ 6/16/92	
DRAWN	PR-20431	
	TSM 14DEC92	
CHECK	CHECK	
	CHECK	
DRAWN	14 DEC 92	
	TSM	


**NOTES**

- ① MOUNTING HOLES WILL ACCEPT .087 MAX Ø PINS OR SCREWS ON .188 ±.002 CENTERS
- ② ACTUATION IN LINE WITH ARROW "A" IS RECOMMENDED
- ③ WEIGHT OF SWITCH ONLY IS .16 OZ MAX. WEIGHT OF SWITCH, WITH WIRE LEADS IS .55 OZ MAX
- ④ - WIRE LEADS MARKED WITH CIRCUIT IDENTIFICATION AND WIRE GAGE (NO-22, C-22, AND NC-22) PER MIL-W-5088
- ⑤ YELLOW MARKING IS ON BOTH SIDES OF HOUSING TO IDENTIFY THAT THIS UNIT HAS GOLD CONTACTS

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS	ELECTRICAL DATA	SCALE 2:1	DO NOT SCALE PRINT
OPERATING FORCE — — — — — 5-17OZ	CONTACT ARRANGEMENT SPDT	<b>UNLESS OTHERWISE SPECIFIED TOLERANCES ARE</b> ONE PLACE (.0) ±.030 TWO PLACE (.00) ±.015 THREE PLACE (.000) ±.005 ANGLES ±	WEIGHT ③
RELEASE FORCE — — — — — 4 OZ MIN	28 VOLTS DC RATING		
RELEASE TRAVEL — — — — — .004 MIN	INDUCTIVE --- SEA LEVEL --- 1/2 AMP		
DIFFERENTIAL TRAVEL — — — — — .005 MAX	50,000 FT --- 1/2 AMP		
OVERTRAVEL — — — — — .004 MIN	RESISTIVE --- SEA LEVEL --- 1 AMP		
	50,000 FT --- 1 AMP		