



## **SUMMARY**

#### # Wires



Image is for illustrative purpose only

Series 2B

Termination type No contacts / Accessory

IP rating (

AWG wire size 0.00 - 0.00

Cable Ø 7.80 - 8.80 mm

**Status** active

#### **Download**

Request a quote

Catalog

## **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model GMA\*: Bend relief Black

**Keying** No keying

Housing Material Thermoplastic polyurethane elastomer (Desmopan 786)

Variant N: Black

Weight 1.82 g

#### **Performance**

Configuration

Insulator

**Rated Current** 


#### **Others**

Temp (min / max):  $-40^{\circ}$ C /  $+80^{\circ}$ C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## **DRAWINGS**

**Draws** 



No keying

#### **Dimensions**

	A	L
mm.	7.8	36
in.	0.31	1.42

# **RECOMMENDED BY LEMO**

**Tools** 

**Cables** 

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.