

Product Search Data Sheet

1.2±0.2

1.2±0.2

(1): Unbalanced (2): GND (3)(4): Balanced : Electrode (in mm) Note: This datasheet may be out of date

Please download the latest datasheet of DXW21BZ7511S#from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=DXW21BZ7511S%23


DXW21BZ7511S#

"#" indicates a package specification code.

In Production RoHS REACH 0200

< List of part numbers with package codes > DXW21BZ7511SL DXW21BZ7511SK DXW21BZ7511SB





- 1. Ultra miniature size and wire wound type microchip transformer. 2.0x1.2x1.2mm (EIAcode:0805)
- 2. Using for GHz frequency range (1 to 1.5GHz) about BS or CS broadcast.
- 3. Surface mount type. Lead Free.



| Automotive Usage |
|---------------------|
|---------------------|

Packaging Information

| Packaging | Specifications | Minimum Order Quantity |
|-----------|---------------------|---------------------------|
| L | 180mm Embossed Tape | 2000 |
| К | 330mm Embossed Tape | 10000 |
| В | Bulk(Bag) | 500 |

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

Please download the latest datasheet of DXW21BZ7511S#from the official website of Murata Manufacturing Co., I to

Ltd. https://www.murata.com/en-us/products/productdetail?partno=DXW21BZ7511S%23

DXW21BZ7511S#

"#" indicates a package specification code.

Specifications

| Operating Temperature Range | -40°C to 105°C | | Insulation Resistance(min.) |
|-----------------------------|----------------------------|---|-----------------------------|
| Frequency Range | 1GHz to 1.5GHz | - | Mass(typ.) |
| Insertion Loss | 1.4dB max.(at Freq. Range) | | |
| Size Code (in mm) | 2012 | | |
| Size Code (in inch) | 0805 | | |
| Length | 2mm | | |
| Length Tolerance | ±0.2mm | | |
| Width | 1.2mm | | |
| Width Tolerance | ±0.2mm | | |
| Thickness | 1.2mm | | |
| Thickness Tolerance | ±0.2mm | | |
| Power Rating | 27dBm | | |
| Rated Voltage | 20Vdc | | |
| Withstanding Voltage | 50Vdc | | |
| Port Impedance | 75Ω - 75Ω | | |
| CMRR(min.) | 20dB | | |
| DC Resistance(max.) | 0.59Ω | | |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product and inserts before ordering.

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

Please download the latest datasheet of DXW21BZ7511S#from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-us/products/productdetail?partno=DXW21BZ7511S%23


DXW21BZ7511S#

"#" indicates a package specification code.




INNOVATOR IN FLECT





Insertion Loss Characteristics





Equivalent Circuit

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

