

Search Results

- Evaluate
  - FAQ's
- Design a Solution
  - Part Drawings
  - PDFNon-Shrink P ..
- How to Buy
  - Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'TV105-.50D20Y'

Your search criteria matched only one product, shown below

**TV105-.50D20Y**



- Non-Shrink oil resistant flexible clear tubing on reel
- Provides insulation and protection for lead wires wire harness assemblies soldered joints and components in electrical and electronic equipment
  - Material: Polyvinyl chloride (PVC)
  - Voltage Rating: 300V and 600V
  - All purpose flexible non -shrinkable
  - Resistant to heat and moisture
- Applicable Specifications:
- UL224 VW-1
  - CSA C22.2 No. 198.1 (OFT)
  - ASTM D-922 Grade CFR
  - MIL-I-631 Type F, Form U, Grade C- Class 1 Category 1

Part Number	TV105-.50D20Y
RoHS Compliant Status	Compliant
Note	TV105-.50D20Y replaces TV105-.50TL20Y
Part Description	PVC Non-Shrink Tubing, 105°C rated
Material	Polyvinyl Chloride
Color	Black
CSA Certified	Yes
CSA Specification	CSA C22.2 No. 198.1 (OFT)
UL Recognized	E122770
UL Recognized Specification	UL224 VW-1
CE Compliant	No
CE Marking	No
Flammability Rating	UL224 VW-1
Length Per Reel (ft.)	500
Length Per Reel (m)	152.4
Max. Inside Diameter (In.)	.524
Max. Inside Diameter (mm)	13.30
Max. Voltage Rating	600 V
Min. Inside Diameter (mm)	12.70
Minimum Inside Diameter (In.)	.500
Nominal Size	1/2
Pricing Description	Vinyl Tubing, .50" (12.7mm), 600V, Black
Temperature Range	-4°F to 221°F (-20°C to 105°C)
Wall Thickness (In.)	.025
Wall Thickness (mm)	.64
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.