

## Minicom PX USB - Remote KVM access with Power-on-Cable (POC)

MODEL NUMBER: 0SU70068



### Description

Complete access to your computer - any time, anywhere

Completing the OOB Remote Support package

Virtual Media capability for each server

Complete remote support for mission critical applications

Scalable centralized management

### Features

- Single port, palm-sized device
- Virtual Media for complete remote management
- Absolute Mouse Support for reduced installation hassle
- BIOS level access over IP connection
- Management system enabled

### Highlights

- Single port, palm-sized device
- Virtual Media for complete remote management
- Absolute Mouse Support for reduced installation hassle
- BIOS level access over IP connection
- Management system enabled
- Cost-effective & easily scalable
- Ideal for isolated/widely distributed servers
- Power over Ethernet & external power option
- Includes one Power-on-Cable (POC) - Model #0SU60020
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### System Requirements

#### Operating System

- Compatible with Windows 98 and higher, Novell, Linux, SUN Solaris and Mac

#### Resolution

- Host Computer: Supports video resolutions up to 1600 x 1200 @ 85Hz
- Client Computer: Recommended - client computer resolution should be higher than resolution on the host computer

### Package Includes

- PX USB
- Power-on-Cable (POC)



- Cost-effective & easily scalable
- Ideal for isolated/widely distributed servers
- Power over Ethernet & external power option
- Includes one Power-on-Cable (POC) - Model #0SU60020
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

- USB Cable Kit
- Rackmount Hardware
- Owner's Manual

## Specifications

OVERVIEW	
UPC Code	654518212174
PHYSICAL	
Color	Silver
Shipping Dimensions (hwd / cm)	19.05 x 18.29 x 3.81
Shipping Dimensions (hwd / in.)	7.50 x 7.20 x 1.50
Shipping Weight (kg)	1.04
Shipping Weight (lbs.)	2.30
Unit Dimensions (hwd / cm)	3.3 x 1.05 x 8
Unit Dimensions (hwd / in.)	1.2 x 4.13 x 3.15
Unit Weight (kg)	0.30
Unit Weight (lbs.)	0.66
ENVIRONMENTAL	
Storage Temperature Range	-40°C to 70°C / -40°F to 158°F
Relative Humidity	80% Non-Condensing
Operating Temperature	0°C to 40°C / 32°F to 104°F
CONNECTIONS	
PC/Server Connections	VGA; USB; PS/2
FEATURES & SPECIFICATIONS	
Number of Users	1
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>