

Designed to be used with B070-008-19, B070-016-19, B072-008-1, B072-008-1A, B072-016-1 or B072-016-1A NetCommander Cat5 KVM switches. Not for use with B070-008-19-IP, B070-016-19-IP, B072-008-1-IP or B072-016-1-IP NetCommander IP Cat5 KVM Switches

# **KVM Switch Accessories - NetCommander USB Server Interface Unit (SIU)**

MODEL NUMBER: B078-101-USB



# Description

The Tripp Lite NetCommander USB Server Interface Unit (SIU) connects to the HD15 port and USB port on a computer/server, and converts them to a single RJ45 connector. Ordinary Cat5e patch cables can then be used to connect the server to the switch ports on a Tripp Lite B070-008-19, B070-016-19, B072-008-1, B072-008-1A, B072-016-1 or B072-016-1A NetCommander Cat5 KVM switch. Use of Cat5e cables frees up space in the installation that would ordinarily be filled by traditional, thicker KVM cables.

#### **Features**

- Needed to connect a USB Server to a B070-008-19, B070-016-19, B072-008-1, B072-008-1A, B072-016-1 or B072-016-1A NetCommander KVM switch via Cat5e cable
- Eliminates the need for thicker, heavier KVM cables
- Compact, lightweight design
- Plug and Play; no software required
- No power supply required
- Allows a Server/CPU to be located up to 100ft away from the KVM switch

## **Highlights**

- Needed to connect a USB
  Server to a B070-008-19, B070-016-19, B072-008-1, B072-008-1A, B072-016-1 or B072-016-1A
  NetCommander KVM switch via Cat5e cable
- Easy to install; no software needed
- No power supply required
- Allows a recommended maximum distance of 100ft from KVM to computer/server via
   Cat5e cable
- Compact and lightweight design

#### **System Requirements**

- Server or CPU with a HD15 port and a USB port
- A B070-008-19, B070-016-19, B072-008-1, B072-008-1A, B072-016-1 or B072-016-1A NetCommander Cat5 KVM
   Switch
- Not for use with B070-008-19-IP, B070-016-19-IP, B072-008-1-IP or B072-016-1-IP
  NetCommander IP Cat5 KVM
  Switches
- Cat5e/6 cable; up to 100ft

### Package Includes

(x1) B078-101-USB USB Server
 Interface Unit (SIU)

# **Specifications**

**OVERVIEW** 





UPC Code	037332148421
PHYSICAL	
Shipping Dimensions (hwd / cm)	9.14 x 4.06 x 2.29
Shipping Dimensions (hwd / in.)	3.60 x 1.60 x 0.90
Shipping Weight (kg)	0.18
Shipping Weight (lbs.)	0.40
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>