

**Tripp Lite** 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

## HDMI Display-Side Wallplate with Active Signal Booster, White (F/F)

### MODEL NUMBER: P166-001-A











#### Description

Tripp Lite's P166-001-A HDMI Display-side Wallplate with Signal Booster increases the distance a 1080p (24Hz) signal can be transmitted beyond the recommended 16 ft. (5 m.). It supports video resolutions up to 1080p, and a maximum distance of 150 ft. from the source. Use P568-Series HDMI cables in most applications. When extending a 1080p (24Hz) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD. (Lengths over 100 ft. are available from Tripp Lite as a custom order) 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable. Simply connect the longer cable between the source and the P166-001-A, and the shorter cable (16 ft. or less) between the adapter and the monitor. Software or drivers are not required. HDCP compliant.

#### Features

- Cleans up Home Theater installations by hiding HDMI Cables
- · Wallplate is the size of a standard electrical outlet
- Extend a 1080p (24Hz) HDMI signal up to 150 ft. from the source
- Use P568-Series HDMI cables in most applications
- When extending a 1080p (24Hz) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD. (Lengths over 100 ft. are available from Tripp Lite as a custom order)
- 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable
- Supports DTS-HD, Dolby True HD and 7.1 Channel Surround Sound Audio
- HDCP compliant
- · No software or drivers required

#### **Highlights**

- Extend a 1080p (24Hz) HDMI signal up to 150 ft. from the source
- When extending a 1080p (24Hz) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD
- 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable
- Supports DTS-HD, Dolby True HD and 7.1 Channel Surround Sound Audio

#### **Package Includes**

• HDMI Display-side Wallplate w/Signal Booster



# **Specifications**

| OVERVIEW                               |                         |
|--|-------------------------|
| UPC Code                               | 037332141033            |
| PHYSICAL                               |                         |
| Color                                  | White                   |
| Shipping Dimensions (hwd / cm)         | 17.78 x 22.86 x 1.27    |
| Shipping Dimensions (hwd / in.)        | 7.00 x 9.00 x 0.50      |
| Shipping Weight (kg)                   | 0.06                    |
| Shipping Weight (lbs.)                 | 0.14                    |
| CONNECTIONS                            |                         |
| Side A - Connector 1                   | HDMI (FEMALE)           |
| Side B - Connector 1                   | HDMI (FEMALE)           |
| FEATURES & SPECIFICATIONS              |                         |
| Technology                             | НДМІ                    |
| WARRANTY                               |                         |
| Product Warranty Period<br>(Worldwide) | 3-year limited warranty |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies