



Keywords Search:

GO!

- ▶ [New Product](#)
- ▶ [1U Redundant](#)
- ▶ [1U Single](#)
- ▶ [2U Redundant](#)
- ▶ [2U Single](#)
- ▶ [3U Single](#)
- ▶ [Cloud Power](#)
- ▶ [Easy Swap](#)
- ▶ [Medical](#)
- ▶ [Micro Redundant](#)
- ▶ [Mini 1U Single](#)
- ▶ [Mini Redundant](#)
- ▶ [N+1 Redundant](#)
- ▶ [Open Frame](#)
- ▶ [PS2](#)
- ▶ [PS2\\*2 Redundant](#)
- ▶ [PS2+](#)
- ▶ [Redundant module](#)

## Products

Search:

Select Select Select Select

【1U Single】P1H-6400P



### Output Wattage...

400W

### Best Solution for...

Server ,Workstation ,Storage System ,IPC

Inquiry

### Dimension...

225x100x40.5(mm)  
8.85x3.94x1.59(inch)

### Input Spec...

VOLTAGE: 90 ~ 264 VAC FULL RANGE

### DC Output Spec...

Output Voltage	Output Current Min.	Output Current Max.	Regulation Load	Regulation Line	Output Ripple & Noise Max.[P-P]
5V	3	25	± 5%	± 1%	80mV
12V	2	28	± 6%	± 1%	120mV
-5V	0	0.5	±10%	± 1%	150mV
-12V	0	0.5	±10%	± 1%	150mV
3.3V	1	20	± 5%	± 1%	80mV
+5VSB	0.1	2	± 5%	± 1%	80mV

REMARKS: THE OUTPUT POWER OF 5V & 3.3V NOT EXCEED 175W

### Features...

- \*Active PFC (full range), MEET IEC-1000-3-2 CLASS D
- \*12V Max. Current : 28A
- \*TEMPERATURE RANGE: OPERATING 0°C ~ 40°C
- \* HUMIDITY:OPERATING:20%-95%, NON-OPERATING:10%-95%
- \* REMARKS:85% IS NORMAL CONDITION AND 95% IS WITH SPECIAL COATING PROCESS
- \*EMI NOISE FILTER: FCC CLASS B, CISPR22 CLASS B
- \*SAFETY: UL 1950, CSA 22.2 NO/ 950, TUV IEC 950
- \*Remote on/off control
- \*Cooling: Dual 40 mm DC Fans
- \*3.3V /5V Remote sensing
- \*Serial ATA optional

\*THE POWER-SUPPLY IS FOR CHASSIS-ASSEMBLY ONLY AND IS NOT ALLOWED TO BE OPERATED AS STAND-ALONE COMPONENT. FINAL ASSEMBLY HAS TO COMPLY WITH CORRESPONDING EMC- AND SAFETY-REGULATIONS.

### Download

- [DRAWING](#)
- [CB](#)
- [CCC](#)
- [TUV](#)
- [MTBF](#)
- [FCC](#)
- [CE](#)
- [MTBF\(RoHS\)](#)
- [CE\(Radiation\)](#)
- [FCC](#)
- [MTBF\(RoHS\)\(40°C\)](#)